

Surface Sensor for High Rel & Aerospace

2 to 100K Ohms Resistance @25°C
 Excellent Stability
 Flight Heritage
 Robust Construction
 Non ITAR Restrictive
 Flat Surface for Ease of Mounting
 Approved by Prime Contractors



HIGH REL SURFACE SENSOR


Matched Glass Coated NTC Thermistor Beads mounted on an aluminum housing and encapsulated in Stycast 2850FT epoxy. Wire connection is by 26AWG stranded / insulated leads. Lead wire is in accordance with ESCC Detail Specification no. 3901/012 variant 03.

FEATURES

- Flat aluminum housing
- Radiation cross linked modified fluoropolymer insulation
- Temperature range -40°C to +125°C

APPLICATIONS

- Satellite electric motors.
- Monitoring of gearboxes in satellites.
- Temperature compensation.
- Battery power packs.
- Vision systems
- Panel temperature measurement
- Monitoring of actuators



Note: Refer to individual datasheets for dimensions

Surface Sensor for High Rel & Aerospace

Part Number	Resistance [Ω] @ +25°C	Tolerance from 0 to +100°C	Beta Value 0/50	Dissipation Constant in still air @ +25°C	Time response (Air)
G2K7D411	2,000	±0.35°C	3422	2 mW/°C	<25 seconds
G4K7D421	4,000	±0.35°C	3422	2 mW/°C	<25 seconds
G10K4D453	10,000	±0.35°C	3575	2 mW/°C	<25 seconds
G15K4D489	15,000	±0.35°C	3575	2 mW/°C	<25 seconds
G100K6D487	100,000	±0.35°C	4143	2 mW/°C	<25 seconds

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

Ordering Information