




**Panasonic**  
ideas for life

**LOW PROFILE  
2 FORM C & 4 FORM C  
RELAY**

**TQ RELAYS**



**RoHS Directive compatibility information**  
<http://www.mew.co.jp/ac/e/environment/>

**2. Nominal operating power: High sensitivity of 140mW (2 Form C single side stable type)**  
By using the highly efficient polar magnetic circuit "seesaw balance mechanism", a nominal operating power of 140 mW (minimum operating power of 79 mW) has been achieved (4 Form C single side stable type is 280 mW).

**3. Suitable for SMD automatic insertion (SA type)**  
With a height of 5.6 mm .220 inch, the relays meet JIS C 0806 specifications.

**4. High density mounting possible**  
High-efficiency magnetic circuits ensure low magnetic flux leakage. Because characteristics are little changed by proximity mounting, high-density mounting is possible.

**5. The use of gold-clad twin crossbar contacts ensures high contact reliability.**

**6. DIL terminal array enables use of IC sockets**

**7. Low thermal electromotive force**  
As well as low power consumption of 140 mW, use of a structure with separate coil and contact sections has reduced thermal electromotive force to the low level of approximately 5 μV.

Surface mount types achieve approximately 2 μV.

**8. Latching types also available**

**9. Self-clinching terminal also available**

**10. A range of surface-mount types is also available.**

SA: Low-profile surface-mount terminal type

SL: High connection reliability surface-mount terminal type

SS: Space saving surface-mount terminal type

**11. M.B.B. contact types available**

## FEATURES

### 1. Flat compact size

14.0(L) × 9.0(W) × 5.0(H) .551(L) × .354(W) × .197(H)

## ORDERING INFORMATION

Contact arrangement

2: 2 Form C

4: 4 Form C

Terminal shape

Nil: Standard PC board terminal

H: Self-clinching terminal

SA: SA type

SL: SL type

SS: SS type

Operating function

Nil: Single side stable

L: 1 coil latching

L2: 2 coil latching

MBB function

Nil: Standard (B.B.M.) type

2M: 2M.B.B. type

Coil voltage (DC)\*

1.5 (SMD only), 3, 4.5, 5, 6, 9, 12, 24, 48V

Packing style

Nil: Tube packing

X: Tape and reel (picked from 1/2/3/4/5-pin side)

Z: Tape and reel packing (picked from the 6/7/8/9/10-pin side)

Notes: 1. \*48 V coil type: Single side stable only

2. In case of 5 V transistor drive circuit, it is recommended to use 4.5 V type relay.

TQ 2 [ ] - [ ] - [ ] - [ ] - [ ]

TQ

## I. Standard PC board terminal and self-clinching terminal

### TYPES

#### 1. Standard (B.B.M.) type

##### 1) Standard PC board terminal

| Contact arrangement | Nominal coil voltage | Single side stable | 1 coil latching | 2 coil latching |
|---------------------|----------------------|--------------------|-----------------|-----------------|
|                     |                      | Part No.           | Part No.        | Part No.        |
| 2 Form C            | 3V DC                | TQ2-3V             | TQ2-L-3V        | TQ2-L2-3V       |
|                     | 4.5V DC              | TQ2-4.5V           | TQ2-L-4.5V      | TQ2-L2-4.5V     |
|                     | 5V DC                | TQ2-5V             | TQ2-L-5V        | TQ2-L2-5V       |
|                     | 6V DC                | TQ2-6V             | TQ2-L-6V        | TQ2-L2-6V       |
|                     | 9V DC                | TQ2-9V             | TQ2-L-9V        | TQ2-L2-9V       |
|                     | 12V DC               | TQ2-12V            | TQ2-L-12V       | TQ2-L2-12V      |
|                     | 24V DC               | TQ2-24V            | TQ2-L-24V       | TQ2-L2-24V      |
|                     | 48V DC               | TQ2-48V            | —               | —               |
| 4 Form C            | 3V DC                | TQ4-3V             | TQ4-L-3V        | TQ4-L2-3V       |
|                     | 4.5V DC              | TQ4-4.5V           | TQ4-L-4.5V      | TQ4-L2-4.5V     |
|                     | 5V DC                | TQ4-5V             | TQ4-L-5V        | TQ4-L2-5V       |
|                     | 6V DC                | TQ4-6V             | TQ4-L-6V        | TQ4-L2-6V       |
|                     | 9V DC                | TQ4-9V             | TQ4-L-9V        | TQ4-L2-9V       |
|                     | 12V DC               | TQ4-12V            | TQ4-L-12V       | TQ4-L2-12V      |
|                     | 24V DC               | TQ4-24V            | TQ4-L-24V       | TQ4-L2-24V      |
|                     | 48V DC               | TQ4-48V            | —               | —               |

Standard packing (2 Form C): Tube: 50 pcs.; Case: 1,000 pcs.

Standard packing (4 Form C): Tube: 25 pcs.; Case: 500 pcs.

##### 2) Self-clinching terminal

| Contact arrangement | Nominal coil voltage | Single side stable | 1 coil latching | 2 coil latching |
|---------------------|----------------------|--------------------|-----------------|-----------------|
|                     |                      | Part No.           | Part No.        | Part No.        |
| 2 Form C            | 3V DC                | TQ2H-3V            | TQ2H-L-3V       | TQ2H-L2-1.5V    |
|                     | 4.5V DC              | TQ2H-4.5V          | TQ2H-L-4.5V     | TQ2H-L2-3V      |
|                     | 5V DC                | TQ2H-5V            | TQ2H-L-5V       | TQ2H-L2-4.5V    |
|                     | 6V DC                | TQ2H-6V            | TQ2H-L-6V       | TQ2H-L2-6V      |
|                     | 9V DC                | TQ2H-9V            | TQ2H-L-9V       | TQ2H-L2-9V      |
|                     | 12V DC               | TQ2H-12V           | TQ2H-L-12V      | TQ2H-L2-12V     |
|                     | 24V DC               | TQ2H-24V           | TQ2H-L-24V      | TQ2H-L2-24V     |
|                     | 48V DC               | TQ2H-48V           | —               | —               |
| 4 Form C            | 3V DC                | TQ4H-3V            | TQ4H-L-3V       | TQ4H-L2-3V      |
|                     | 4.5V DC              | TQ4H-4.5V          | TQ4H-L-4.5V     | TQ4H-L2-4.5V    |
|                     | 5V DC                | TQ4H-5V            | TQ4H-L-5V       | TQ4H-L2-5V      |
|                     | 6V DC                | TQ4H-6V            | TQ4H-L-6V       | TQ4H-L2-6V      |
|                     | 9V DC                | TQ4H-9V            | TQ4H-L-9V       | TQ4H-L2-9V      |
|                     | 12V DC               | TQ4H-12V           | TQ4H-L-12V      | TQ4H-L2-12V     |
|                     | 24V DC               | TQ4H-24V           | TQ4H-L-24V      | TQ4H-L2-24V     |
|                     | 48V DC               | TQ4H-48V           | —               | —               |

Note: Types ("-3" to the end of part No.) designed to withstand strong vibration caused, for example, by the use of terminal cutters, can also be ordered. However, please contact us if you need parts for use in low level load.

#### 2. M.B.B. type

##### 1) Standard PC board terminal

| Contact arrangement | Nominal coil voltage | Single side stable |
|---------------------|----------------------|--------------------|
|                     |                      | Part No.           |
| 2 Form C            | 3V DC                | TQ2-2M-3V          |
|                     | 4.5V DC              | TQ2-2M-4.5V        |
|                     | 5V DC                | TQ2-2M-5V          |
|                     | 6V DC                | TQ2-2M-6V          |
|                     | 9V DC                | TQ2-2M-9V          |
|                     | 12V DC               | TQ2-2M-12V         |
|                     | 24V DC               | TQ2-2M-24V         |

Standard packing: Tube: 50 pcs.; Case: 1,000 pcs.

## 2) Self-clinching terminal

| Contact arrangement | Nominal coil voltage | Single side stable |
|---------------------|----------------------|--------------------|
|                     |                      | Part No.           |
| 2 Form C            | 3V DC                | TQ2H-2M-3V         |
|                     | 4.5V DC              | TQ2H-2M-4.5V       |
|                     | 5V DC                | TQ2H-2M-5V         |
|                     | 6V DC                | TQ2H-2M-6V         |
|                     | 9V DC                | TQ2H-2M-9V         |
|                     | 12V DC               | TQ2H-2M-12V        |
|                     | 24V DC               | TQ2H-2M-24V        |

Standard packing: Tube: 50 pcs.; Case: 1,000 pcs.

Notes: 1. Latching types are available by request. Please consult us for details.

2. UL/CSA approved (UL file No.:E 43149, CSA file No.: LR26550)

3. Types ("1" to the end of part No.) designed to withstand strong vibration caused, for example, by the use of terminal cutters, can also be ordered. However, please contact us if you need parts for use in low level load and low thermal power.

## RATING

## 1. Coil data

## [Standard (B.B.M.) type]

## 1) Single side stable (2 Form C)

| Nominal coil voltage | Pick-up voltage (at 20°C 68°F)             | Drop-out voltage (at 20°C 68°F)            | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|---|-------------------------|---------------------------------------|
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 10%V or more of nominal voltage* (Initial) | 46.7mA  | 64.3 $\Omega$                                 | 140mW                   | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 31.1mA  | 144.6 $\Omega$                                |                         |                                       |
| 5V DC                |  |  | 28.1mA  | 178 $\Omega$                                  |                         |                                       |
| 6V DC                |  |  | 23.3mA  | 257 $\Omega$                                  |                         |                                       |
| 9V DC                |  |  | 15.5mA  | 579 $\Omega$                                  |                         |                                       |
| 12V DC               |  |  | 11.7mA  | 1,028 $\Omega$                                |                         |                                       |
| 24V DC               |  |  | 8.3mA   | 2,880 $\Omega$                                | 200mW                   |                                       |
| 48V DC               |  |  | 6.25mA  | 7,680 $\Omega$                                | 300mW                   | 120%V of nominal voltage              |

## 2) 1 coil latching (2 Form C)

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|---|-------------------------|---------------------------------------|
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 33.3mA  | 90 $\Omega$                                   | 100mW                   | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 22.2mA  | 202.5 $\Omega$                                |                         |                                       |
| 5V DC                |  |  | 20mA  | 250 $\Omega$                                  |                         |                                       |
| 6V DC                |  |  | 16.7mA  | 360 $\Omega$                                  |                         |                                       |
| 9V DC                |  |  | 11.1mA  | 810 $\Omega$                                  |                         |                                       |
| 12V DC               |  |  | 8.3mA   | 1,440 $\Omega$                                |                         |                                       |
| 24V DC               |  |  | 6.3mA   | 3,840 $\Omega$                                | 150mW                   |                                       |

## 3) 2 coil latching (2 Form C)

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) |            | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) |                | Nominal operating power |            | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|------------|---|----------------|-------------------------|------------|---------------------------------------|
|                      |  |  | Set coil  | Reset coil | Set coil                                      | Reset coil     | Set coil                | Reset coil |                                       |
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 66.7mA  | 66.7mA     | 45 $\Omega$                                   | 45 $\Omega$    | 200mW                   | 200mW      | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 44.4mA  | 44.4mA     | 101.2 $\Omega$                                | 101.2 $\Omega$ |                         |            |                                       |
| 5V DC                |  |  | 40mA  | 40mA       | 125 $\Omega$                                  | 125 $\Omega$   |                         |            |                                       |
| 6V DC                |  |  | 33.3mA  | 33.3mA     | 180 $\Omega$                                  | 180 $\Omega$   |                         |            |                                       |
| 9V DC                |  |  | 22.2mA  | 22.2mA     | 405 $\Omega$                                  | 405 $\Omega$   |                         |            |                                       |
| 12V DC               |  |  | 16.7mA  | 16.7mA     | 720 $\Omega$                                  | 720 $\Omega$   |                         |            |                                       |
| 24V DC               |  |  | 12.5mA  | 12.5mA     | 1,920 $\Omega$                                | 1,920 $\Omega$ | 300mW                   | 300mW      | 120%V of nominal voltage              |

## 4) Single side stable (4 Form C)

| Nominal coil voltage | Pick-up voltage (at 20°C 68°F)             | Drop-out voltage (at 20°C 68°F)            | Nominal operating current [ $\pm 10\%$ ] (at 20°C 68°F) | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|---|-------------------------|---------------------------------------|
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 10%V or more of nominal voltage* (Initial) | 93.8mA  | 32 $\Omega$                                   | 280mW                   | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 62.2mA  | 72.3 $\Omega$                                 |                         |                                       |
| 5V DC                |  |  | 56.2mA  | 89 $\Omega$                                   |                         |                                       |
| 6V DC                |  |  | 46.5mA  | 129 $\Omega$                                  |                         |                                       |
| 9V DC                |  |  | 31.1mA  | 289 $\Omega$                                  |                         |                                       |
| 12V DC               |  |  | 23.3mA  | 514 $\Omega$                                  |                         |                                       |
| 24V DC               |  |  | 11.7mA  | 2,056 $\Omega$                                |                         |                                       |
| 48V DC               |  |  | 8.3mA   | 5,760 $\Omega$                                | 400mW                   | 120%V of nominal voltage              |

TQ

## 5) 1 coil latching (4 Form C)

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current [±10%] (at 20°C 68°F) | Coil resistance [±10%] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|---------------------------------------|-------------------------|---------------------------------------|
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 66.6mA  | 45Ω                                   | 200mW                   | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 44.4mA  | 101.2Ω                                |                         |                                       |
| 5V DC                |  |  | 40mA  | 125Ω                                  |                         |                                       |
| 6V DC                |  |  | 33.3mA  | 180Ω                                  |                         |                                       |
| 9V DC                |  |  | 22.2mA  | 405Ω                                  |                         |                                       |
| 12V DC               |  |  | 16.7mA  | 720Ω                                  |                         |                                       |
| 24V DC               |  |  | 8.3mA   | 2,880Ω                                |                         |                                       |

## 6) 2 coil latching (4 Form C)

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current [±10%] (at 20°C 68°F) |            | Coil resistance [±10%] (at 20°C 68°F) |            | Nominal operating power |            | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|------------|---------------------------------------|------------|-------------------------|------------|---------------------------------------|
|                      |  |  | Set coil  | Reset coil | Set coil                              | Reset coil | Set coil                | Reset coil |                                       |
| 3V DC                | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 133mA   | 133mA      | 22.5Ω                                 | 22.5Ω      | 400mW                   | 400mW      | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 88.9mA  | 88.9mA     | 50.6Ω                                 | 50.6Ω      |                         |            |                                       |
| 5V DC                |  |  | 80mA  | 80mA       | 62.5Ω                                 | 62.5Ω      |                         |            |                                       |
| 6V DC                |  |  | 66.6mA  | 66.6mA     | 90Ω                                   | 90Ω        |                         |            |                                       |
| 9V DC                |  |  | 44.4mA  | 44.4mA     | 202.5Ω                                | 202.5Ω     |                         |            |                                       |
| 12V DC               |  |  | 33.3mA  | 33.3mA     | 360Ω                                  | 360Ω       |                         |            |                                       |
| 24V DC               |  |  | 16.7mA  | 16.7mA     | 1,440Ω                                | 1,440Ω     |                         |            |                                       |

\*Pulse drive (JIS C 5442-1986)

## [M.B.B. type]

| Nominal coil voltage | Pick-up voltage (at 20°C 68°F)             | Drop-out voltage (at 20°C 68°F)            | Nominal operating current [±10%] (at 20°C 68°F) | Coil resistance [±10%] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|---|---------------------------------------|-------------------------|---------------------------------------|
| 3V DC                | 80%V or less of nominal voltage* (Initial) | 10%V or more of nominal voltage* (Initial) | 66.7mA  | 45Ω                                   | 200mW                   | 150%V of nominal voltage              |
| 4.5V DC              |  |  | 44.4mA  | 101Ω                                  |                         |                                       |
| 5V DC                |  |  | 40mA  | 125Ω                                  |                         |                                       |
| 6V DC                |  |  | 33.3mA  | 180Ω                                  |                         |                                       |
| 9V DC                |  |  | 22.2mA  | 405Ω                                  |                         |                                       |
| 12V DC               |  |  | 16.7mA  | 720Ω                                  |                         |                                       |
| 24V DC               |  |  | 8.3mA   | 2,880Ω                                |                         |                                       |

\*Pulse drive (JIS C 5442-1986)

**2. Specifications**

| Characteristics                          | Item  | Specifications   |  |   |
|--|---|--|--|---|
|  |   | 2 Form C, 2 Form D (M.B.B.)  | 4 Form C   |   |
| Contact                                  | Arrangement   | 2 Form C, 2 Form D (M.B.B.)  |  |   |
|  | Initial contact resistance, max.  | Max. 50mΩ (By voltage drop 6 V DC 1A)  |  |   |
|  | Contact material  | Ag+Au clad   |  |   |
| Rating                                   | Nominal switching capacity (resistive load)   | 1 A 30 V DC, 0.5 A 125 V AC*1  |  |   |
|  | Max. switching power (resistive load)   | 30 W (DC), 62.5 V A (AC)*1   |  |   |
|  | Max. switching voltage  | 110 V DC, 125 V AC*1   |  |   |
|  | Max. switching current  | 1 A  |  |   |
|  | Min. switching capacity (Reference value)*2   | 10μA 10mV DC   |  |   |
|  | Nominal operating power   | Single side stable   | Standard (B.B.M) type: 140 mW (3 to 12 V DC), 200 mW (24 V DC), 300 mW (48 V DC)<br>M.B.B. type: 200 mW                              | 280 mW (3 to 24 V DC), 400 mW (48 V DC) |
| 1 coil latching                          |   | 100 mW (3 to 12 V DC), 150 mW (24 V DC)  | 200 mW   |   |
| 2 coil latching                          |   | 200 mW (3 to 12 V DC), 300 mW (24 V DC)  | 400 mW   |   |
| Electrical characteristics               | Insulation resistance (Initial)   | Min. 1,000MΩ (at 500V DC)<br>Measurement at same location as "Initial breakdown voltage" section.  |  |   |
|  | Breakdown voltage (Initial)   | Between open contacts  | Standard (B.B.M) type: 750 Vrms for 1min. (Detection current: 10 mA),<br>M.B.B. type: 300 Vrms for 1 min. (Detection current: 10 mA) |   |
|  |   | Between contact and coil   | 1,000 Vrms for 1min. (Detection current: 10 mA)  |   |
|  |   | Between contact sets   | 1,000 Vrms for 1min. (Detection current: 10 mA)  |   |
|  | Temperature rise (at 20°C 68°F)   | Max. 50°C (By resistive method, nominal voltage applied to the coil; contact carrying current: 1A.)  |  |   |
|  | Operate time [Set time] (at 20°C 68°F)  | Max. 3 ms [Max. 3 ms] (Nominal voltage applied to the coil, excluding contact bounce time.)  |  |   |
| Release time [Reset time] (at 20°C 68°F) | Max. 3 ms [Max. 3 ms] (Nominal voltage applied to the coil, excluding contact bounce time.) (without diode) |  |  |   |
| Mechanical characteristics               | Shock resistance  | Functional   | Min. 490 m/s <sup>2</sup> (Half-wave pulse of sine wave: 11 ms; detection time: 10μs.)   |   |
|  |   | Destructive  | Min. 980 m/s <sup>2</sup> (Half-wave pulse of sine wave: 6 ms.)  |   |
|  | Vibration resistance  | Functional   | 10 to 55 Hz at double amplitude of 3 mm (Detection time: 10μs.)  |   |
|  |   | Destructive  | 10 to 55 Hz at double amplitude of 5 mm  |   |
| Expected life                            | Mechanical (at 180 cpm)   | Standard (B.B.M) type: Min. 10 <sup>8</sup> , M.B.B. type: Min. 10 <sup>7</sup>  |  |   |
|  | Electrical (at 20 cpm)  | Standard (B.B.M) type: Min. 2×10 <sup>5</sup> (1 A 30 V DC resistive), Min. 10 <sup>5</sup> (0.5 A 125 V AC resistive)<br>M.B.B. type: Min. 10 <sup>5</sup> (1 A 30 V DC resistive)  |  |   |
| Conditions                               | Conditions for operation, transport and storage*3   | Standard (B.B.M) type:<br>Ambient temperature: -40°C to +70°C -40°F to +158°F;<br>Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature)<br>M.B.B. type:<br>Ambient temperature: -40°C to +50°C -40°F to +122°F;<br>Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature) |  |   |
|  | Max. operating speed (at rated load)  | 20 cpm   |  |   |
| Unit weight                              |   | Approx. 1.5 g .053 oz  | Approx. 3 g .106 oz.   |   |


Notes: \*1 AC is standard (B.B.M) type only.

\*2 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load. (SX relays are available for low level load switching [10V DC, 10mA max. level])


\*3 Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT.

**REFERENCE DATA**

1. Maximum switching capacity




2. Life curve




3. Mechanical life

Tested sample: TQ2-12V, 10 pcs.




4.-(1) Electrical life (DC load)

Tested sample: TQ2-12V, 6 pcs.  
Condition: 1 A 30 V DC resistive load, 20 cpm  
Change of pick-up and drop-out voltage




Change of contact resistance




4.-(2) Electrical life (AC load)

Tested sample: TQ2-12V, 6 pcs.  
Condition: 0.5 A 125 V AC resistive load, 20 cpm  
Change of pick-up and drop-out voltage




Change of contact resistance




5. Coil temperature rise (2C)

Tested sample: TQ2-12V  
Measured portion: Inside the coil  
Ambient temperature: 30°C 86°F




6. Ambient temperature characteristics


Tested sample: TQ2-12V, 5 pcs.



7.-(1) High-frequency characteristics (Isolation)




7.-(2) High-frequency characteristics (Insertion loss)




8. Malfunctional shock (single side stable)


Tested sample: TQ2-12V, 6 pcs.



9.-(1) Influence of adjacent mounting




9.-(2) Influence of adjacent mounting




10. Contact reliability

(1 mA 5 V DC resistive load)  
Tested sample: TQ2-12V  
Condition: Detection level 10 W




11. Actual load test (35 mA 48 V DC wire spring relay load)


Circuit



Change of pick-up and drop-out voltage




Change of contact resistance




12. 0.1 A 53 V DC resistive load test

Change of pick-up and drop-out voltage





Change of contact resistance



13. Distribution of M.B.B. time

Tested sample: TQ2-2M-5V, 85 pcs.



TQ

## II. Surface-mount terminal

## TYPES

## 1) Tube packing

| Contact arrangement | Nominal coil voltage | Single side stable | 1 coil latching | 2 coil latching |
|---------------------|----------------------|--------------------|-----------------|-----------------|
|                     |                      | Part No.           | Part No.        | Part No.        |
| 2c                  | 1.5V DC              | TQ2S□-1.5V         | TQ2S□-L-1.5V    | TQ2S□-L2-1.5V   |
|                     | 3V DC                | TQ2S□-3V           | TQ2S□-L-3V      | TQ2S□-L2-3V     |
|                     | 4.5V DC              | TQ2S□-4.5V         | TQ2S□-L-4.5V    | TQ2S□-L2-4.5V   |
|                     | 5V DC                | TQ2S□-5V           | TQ2S□-L-5V      | TQ2S□-L2-5V     |
|                     | 6V DC                | TQ2S□-6V           | TQ2S□-L-6V      | TQ2S□-L2-6V     |
|                     | 9V DC                | TQ2S□-9V           | TQ2S□-L-9V      | TQ2S□-L2-9V     |
|                     | 12V DC               | TQ2S□-12V          | TQ2S□-L-12V     | TQ2S□-L2-12V    |
|                     | 24V DC               | TQ2S□-24V          | TQ2S□-L-24V     | TQ2S□-L2-24V    |
|                     | 48V DC               | TQ2S□-48V          | —               | —               |

□: For each surface-mounted terminal identification, input the following letter. SA type: A, SL type: L, SS type: S  
Standard packing: Tube: 50 pcs.; Case: 1,000 pcs.

## 2) Tape and reel packing

| Contact arrangement | Nominal coil voltage | Single side stable | 1 coil latching | 2 coil latching |
|---------------------|----------------------|--------------------|-----------------|-----------------|
|                     |                      | Part No.           | Part No.        | Part No.        |
| 2 Form C            | 1.5V DC              | TQ2S□-1.5V-Z       | TQ2S□-L-1.5V-Z  | TQ2S□-L2-1.5V-Z |
|                     | 3V DC                | TQ2S□-3V-Z         | TQ2S□-L-3V-Z    | TQ2S□-L2-3V-Z   |
|                     | 4.5V DC              | TQ2S□-4.5V-Z       | TQ2S□-L-4.5V-Z  | TQ2S□-L2-4.5V-Z |
|                     | 5V DC                | TQ2S□-5V-Z         | TQ2S□-L-5V-Z    | TQ2S□-L2-5V-Z   |
|                     | 6V DC                | TQ2S□-6V-Z         | TQ2S□-L-6V-Z    | TQ2S□-L2-6V-Z   |
|                     | 9V DC                | TQ2S□-9V-Z         | TQ2S□-L-9V-Z    | TQ2S□-L2-9V-Z   |
|                     | 12V DC               | TQ2S□-12V-Z        | TQ2S□-L-12V-Z   | TQ2S□-L2-12V-Z  |
|                     | 24V DC               | TQ2S□-24V-Z        | TQ2S□-L-24V-Z   | TQ2S□-L2-24V-Z  |
|                     | 48V DC               | TQ2S□-48V-Z        | —               | —               |

□: For each surface-mounted terminal identification, input the following letter. SA type: A, SL type: L, SS type: S  
Standard packing: Tape and reel: 500 pcs.; Case: 1,000 pcs.

Note: Tape and reel packing symbol "-Z" is not marked on the relay. "X" type tape and reel packing (picked from 1/2/3/4-pin side) is also available.

## RATING

## 1. Coil data

## 1) Single side stable

| Nominal coil voltage | Pick-up voltage (at 20°C 68°F)             | Drop-out voltage (at 20°C 68°F)            | Nominal operating current (at 20°C 68°F) | Coil resistance [±10%] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|--|---------------------------------------|-------------------------|---------------------------------------|
| 1.5V DC              | 75%V or less of nominal voltage* (Initial) | 10%V or more of nominal voltage* (Initial) | 93.8mA                                   | 16Ω                                   | 140mW                   | 150%V of nominal voltage              |
| 3V DC                |  |  | 46.7mA                                   | 64.3Ω                                 |                         |                                       |
| 4.5V DC              |  |  | 31mA                                     | 145Ω                                  |                         |                                       |
| 5V DC                |  |  | 28.1mA                                   | 178Ω                                  |                         |                                       |
| 6V DC                |  |  | 23.3mA                                   | 257Ω                                  |                         |                                       |
| 9V DC                |  |  | 15.5mA                                   | 579Ω                                  |                         |                                       |
| 12V DC               |  |  | 11.7mA                                   | 1,028Ω                                | 200mW                   |                                       |
| 24V DC               |  |  | 8.3mA                                    | 2,880Ω                                |                         |                                       |
| 48V DC               |  |  | 6.3mA                                    | 7,680Ω                                | 300mW                   | 120%V of nominal voltage              |

## 2) 1 coil latching

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current (at 20°C 68°F) | Coil resistance [±10%] (at 20°C 68°F) | Nominal operating power | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|--|---------------------------------------|-------------------------|---------------------------------------|
| 1.5V DC              | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 46.9mA                                   | 32Ω                                   | 70mW                    | 150%V of nominal voltage              |
| 3V DC                |  |  | 23.3mA                                   | 128.6Ω                                |                         |                                       |
| 4.5V DC              |  |  | 15.6mA                                   | 289.3Ω                                |                         |                                       |
| 5V DC                |  |  | 14mA                                     | 357Ω                                  |                         |                                       |
| 6V DC                |  |  | 11.7mA                                   | 514Ω                                  |                         |                                       |
| 9V DC                |  |  | 7.8mA                                    | 1,157Ω                                |                         |                                       |
| 12V DC               |  |  | 5.8mA                                    | 2,057Ω                                | 100mW                   |                                       |
| 24V DC               |  |  | 4.2mA                                    | 5,760Ω                                |                         |                                       |



## 3) 2 coil latching

| Nominal coil voltage | Set voltage (at 20°C 68°F)                 | Reset voltage (at 20°C 68°F)               | Nominal operating current (at 20°C 68°F) |            | Coil resistance [ $\pm 10\%$ ] (at 20°C 68°F) |                | Nominal operating power |            | Max. allowable voltage (at 20°C 68°F) |
|----------------------|--|--|--|------------|---|----------------|-------------------------|------------|---------------------------------------|
|                      |  |  | Set coil                                 | Reset coil | Set coil                                      | Reset coil     | Set coil                | Reset coil |                                       |
| 1.5V DC              | 75%V or less of nominal voltage* (Initial) | 75%V or less of nominal voltage* (Initial) | 93.8mA                                   | 93.8mA     | 16 $\Omega$                                   | 16 $\Omega$    | 140mW                   | 140mW      | 150%V of nominal voltage              |
| 3V DC                |  |  | 46.7mA                                   | 46.7mA     | 64.3 $\Omega$                                 | 64.3 $\Omega$  |                         |            |                                       |
| 4.5V DC              |  |  | 31mA                                     | 31mA       | 145 $\Omega$                                  | 145 $\Omega$   |                         |            |                                       |
| 5V DC                |  |  | 28.1mA                                   | 28.1mA     | 178 $\Omega$                                  | 178 $\Omega$   |                         |            |                                       |
| 6V DC                |  |  | 23.3mA                                   | 23.3mA     | 257 $\Omega$                                  | 257 $\Omega$   |                         |            |                                       |
| 9V DC                |  |  | 15.5mA                                   | 15.5mA     | 579 $\Omega$                                  | 579 $\Omega$   |                         |            |                                       |
| 12V DC               |  |  | 11.7mA                                   | 11.7mA     | 1,028 $\Omega$                                | 1,028 $\Omega$ |                         |            |                                       |
| 24V DC               |  |  | 8.3mA                                    | 8.3mA      | 2,880 $\Omega$                                | 2,880 $\Omega$ | 200mW                   | 200mW      |                                       |

\*Pulse drive (JIS C 5442-1986)

## 2. Specifications


| Characteristics                          | Item  | Specifications  |   |
|--|---|---|---|
| Contact                                  | Arrangement   | 2 Form C  |   |
|  | Initial contact resistance, max.  | Max. 75 m $\Omega$ (By voltage drop 6 V DC 1A)  |   |
|  | Contact material  | AgNi type+Au clad   |   |
| Rating                                   | Nominal switching capacity (resistive load)   | 2 A 30 V DC, 0.5 A 125 V AC   |   |
|  | Max. switching power (resistive load)   | 60 W (DC), 62.5 VA (AC)   |   |
|  | Max. switching voltage  | 220 V DC, 125 V AC  |   |
|  | Max. switching current  | 2 A   |   |
|  | Min. switching capacity (Reference value)*1   | 10 $\mu$ A 10mV DC  |   |
|  | Nominal operating power   | Single side stable  | 140 mW (1.5 to 12 V DC), 200 mW (24 V DC), 300 mW (48 V DC)                                 |
|  |   | 1 coil latching   | 70 mW (1.5 to 12 V DC), 100 mW (24 V DC)  |
| 2 coil latching                          |   | 140 mW (1.5 to 12 V DC), 200 mW (24 V DC)   |   |
| Electrical characteristics               | Insulation resistance (Initial)   | Min. 1,000M $\Omega$ (at 500V DC)<br>Measurement at same location as "Initial breakdown voltage" section.   |   |
|  | Breakdown voltage (Initial)   | Between open contacts   | 1,000 Vrms for 1 min. (Detection current: 10 mA)  |
|  |   | Between contact and coil  | 1,500 Vrms for 1 min. (Detection current: 10 mA)  |
|  |   | Between contact sets  | 1,500 Vrms for 1 min. (Detection current: 10 mA)  |
|  | Surge breakdown voltage (Initial)   | Between open contacts   | 1,500 V (10 $\times$ 160 $\mu$ s) (FCC Part 68)   |
|  |   | Between contacts and coil   | 2,500 V (2 $\times$ 10 $\mu$ s) (Bellcore)  |
|  | Temperature rise (at 20°C 68°F)   | Max. 50°C<br>(By resistive method, nominal voltage applied to the coil; contact carrying current: 2A.)  |   |
| Operate time [Set time] (at 20°C 68°F)   | Max. 4 ms [Max. 4 ms] (Nominal voltage applied to the coil, excluding contact bounce time.)                 |   |   |
| Release time [Reset time] (at 20°C 68°F) | Max. 4 ms [Max. 4 ms] (Nominal voltage applied to the coil, excluding contact bounce time.) (without diode) |   |   |
| Mechanical characteristics               | Shock resistance  | Functional  | Min. 750 m/s <sup>2</sup> (Half-wave pulse of sine wave: 6 ms; detection time: 10 $\mu$ s.) |
|  |   | Destructive   | Min. 1,000 m/s <sup>2</sup> (Half-wave pulse of sine wave: 6 ms.)                           |
|  | Vibration resistance  | Functional  | 10 to 55 Hz at double amplitude of 3.3 mm (Detection time: 10 $\mu$ s.)                     |
|  |   | Destructive   | 10 to 55 Hz at double amplitude of 5 mm   |
| Expected life                            | Mechanical  | Min. 10 <sup>8</sup> (at 180 cpm)   |   |
|  | Electrical  | Min. 10 <sup>5</sup> (2 A 30 V DC resistive), Min. 2 $\times$ 10 <sup>5</sup> (1 A 30 V DC resistive),<br>Min. 10 <sup>5</sup> (0.5 A 125 V AC resistive) (at 20 cpm)                   |   |
| Conditions                               | Conditions for operation, transport and storage*2   | Ambient temperature:<br>-40°C to +85°C -40°F to +185°F, Max. -40°C to +70°C (2A) Max. -40°F to +158°F (2A);<br>Humidity: 5 to 85% R.H. (Not freezing and condensing at low temperature) |   |
|  | Max. operating speed (at rated load)  | 20 cpm  |   |
| Unit weight                              |   | Approx. 2 g .071 oz   |   |

Notes: \*1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load. (SX relays are available for low level load switching [10V DC, 10mA max. level])


\*2 Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT.

# REFERENCE DATA

## 1. Maximum switching capacity




## 2. Life curve



## 3. Mechanical life (mounting by IRS method)

Tested sample: TQ2SA-12V, 10 pcs.




## 4.-(1) Electrical life (2 A 30 V DC resistive load)


Tested sample: TQ2SA-12V, 6 pcs.

Operating speed: 20 cpm

Change of pick-up and drop-out voltage (mounting by IRS method)



## Change of contact resistance (mounting by IRS method)




## 4.-(2) Electrical life (0.5 A 125 V AC resistive load)


Tested sample: TQ2SA-12V, 6 pcs

Operating speed: 20 cpm

Change of pick-up and drop-out voltage (mounting by IRS method)



## Change of contact resistance (mounting by IRS method)




## 5. Coil temperature rise

Tested sample: TQ2SA-12V, 6 pcs.


Point measured: Inside the coil

Ambient temperature: 25°C 77°F




## 6. Operate/release time

Tested sample: TQ2SA-12V, 6 pcs.




## 7. Ambient temperature characteristics


Tested sample: TQ2SA-12V, 5 pcs.



## 8.-(1) High-frequency characteristics (Isolation)




## 8.-(2) High-frequency characteristics (Insertion loss)




9. Malfunctional shock (single side stable)

Tested sample: TQ2SA-12V, 6 pcs




10.-(1) Influence of adjacent mounting

Tested sample: TQ2SA-12V, 5 pcs.



10.-(2) Influence of adjacent mounting

Tested sample: TQ2SA-12V, 6 pcs.




11. Pulse dialing test


(35 mA 48 V DC wire spring relay load)

Tested sample: TQ2SA-12V, 6 pcs.


Circuit



Change of pick-up and drop-out voltage (mounting by IRS method)




Change of contact resistance (mounting by IRS method)




**DIMENSIONS** (Unit: mm inch)

1. Standard PC board terminal and Self-clinching terminal


1) 2 Form C



External dimensions  
Standard PC board terminal




PC board pattern (Bottom view)



Tolerance:  $\pm 0.1 \pm 0.04$


Self-clinching terminal



General tolerance:  $\pm 0.3 \pm 0.012$


Schematic (Bottom view)

Single side stable




(Deenergized condition)

1-coil latching



(Reset condition)


2-coil latching




(Reset condition)

TQ


2) 4 Form C



External dimensions  
Standard PC board terminal




PC board pattern (Bottom view)




Tolerance:  $\pm 0.1 \pm 0.04$

Self-clinching terminal



General tolerance:  $\pm 0.3 \pm 0.12$

Schematic (Bottom view)




2. Surface-mount terminal



| Type    | External dimensions (General tolerance: $\pm 0.3 \pm 0.12$ ) | Suggested mounting pad (Top view) (Tolerance: $\pm 0.1 \pm 0.04$ ) |
|---------|--|--|
| SA type |  |  |
| SL type |  |  |
| SS type |  |  |

Schematic (Top view)



## NOTES

### 1. Coil operating power

Pure DC current should be applied to the coil. The wave form should be rectangular. If it includes ripple, the ripple factor should be less than 5%. However, check it with the actual circuit since the characteristics may be slightly different. The nominal operating voltage should be applied to the coil for more than 10 ms to set/reset the latching type relay.

### 2. Coil connection


When connecting coils, refer to the wiring diagram to prevent mis-operation or malfunction.

### 3. External magnetic field

Since T series relays are highly sensitive polarized relays, their characteristics will be affected by a strong external magnetic field. Avoid using the relay under that condition.

### 4. Packing style


1) The relay is packed in a tube with the relay orientation mark on the left side, as shown in the figure below.




2) Tape and reel packing (surface-mount terminal type)

(1) Tape dimensions


(i) SA type



(ii) SL, SS type



(2) Dimensions of plastic reel



Note: Dimensions of items produced after December 2006 have changed as shown below.  
100<sup>±1</sup> dia. 3.937<sup>±0.039</sup> dia. → 80<sup>±1</sup> dia. 3.150<sup>±0.039</sup> dia.

### 5. Automatic insertion

To maintain the internal function of the relay, the chucking pressure should not exceed the values below.

Chucking pressure in the direction A:


9.8 N {1 kgf} or less

Chucking pressure in the direction B:

9.8 N {1 kgf} or less

Chucking pressure in the direction C:

9.8 N {1 kgf} or less




Please chuck the portion. Avoid chucking the center of the relay. In addition, excessive chucking pressure to the pinpoint of the relay should be avoided.

### 6. M.B.B. contact relays

A small OFF time may be generated by the contact bounce during contact switching. Check the actual circuit carefully.

If the relay is dropped accidentally, check the appearance and characteristics including M.B.B. time before use.



Measuring condition of M.B.B. time

### 7. Others

1) If in error the relay has been dropped, the appearance and characteristics should be checked before use without fail.

2) The cycle lifetime is defined under the standard test condition specified in the JIS\* C 5442-1986 standard (temperature 15°C to 35°C 59°F to 95°F, humidity 25% to 85%). Check this with the real device as it is affected by coil driving circuit, load type, activation frequency, activation phase, ambient conditions, and other factors.

**For Cautions for Use, see Relay Technical Information.**