



6900GE & 6900PE
 SHIPPING WT.
 APPROX. 16 OZ.
 (467 GRAMS)

基本特性:
 U.L./CSA
 NEMA: 4,7,9,13
 防爆型
 温度 - 34至71°C
 外部设定

6900GE

接口尺寸	1/4"
接口材料	铝合金
隔膜材料	聚丁钠橡胶

最大允许压力 (KG)	设定压力范围 (KG)	压力开关型号	
		SPDT	DPDT
34.48	0.21~1.24	6900GE12	6900GEM12
34.48	0.41~4.90	6900GE14	6900GEM14
103.45	0.83~9.79	6900GE16	6900GEM16
103.45	2.07~24.48	6900GE18	6900GEM18
137.93	20.69~65.52	6900GE20	6900GEM20
206.90	48.28~165.52	6900GE22	6900GEM22

6900PE

接口尺寸	1/4"
接口材料	铝合金
活塞型	聚丁钠橡胶

137.93	1.03~13.10	6900PE32	6900PEM32
206.90	10.34~102.76	6900PE34	6900PEM34
344.83	34.48~208.97	6900PE36	6900PEM36
689.66	137.93~413.79	6900PE38	6900PEM38

接点容量

电压	电流	
	SPDT Res.	DPDT Res.
125AC~50/60Hz	11	11
250AC~50/60Hz	11	11
30DC	5	5
125DC	.5	.5

