

We offer a large standard product line of flexible waveguides covering the waveguides sizes from WR 650 to WR 22. 2 types of flexible waveguides are available:

Type 1: Medium power

Type 2: Seamless for High power applications

These units can be jacketed with silicone rubber or neoprene.



Waveguide	Frequency	Maximum losses (dB/m)	FN - FK pres (Kg/cm2)
WR 650	1,12 - 1,70	0,02	0,5
WR 510	1,45 - 2,20	0,02	1,0
WR 430	1,70 - 2,60	0,03	1,0
WR 340	2,20 - 3,30	0,03	1,0
WR 284	2,60 - 3,95	0,04	1,0
CNET 7	2,82 - 4,29	0,10	1,4
WR 229	3,30 - 4,90	0,08	1,4
WR 187	3,95 - 5,85	0,10	1,4
WR 159	4,90 - 7,05	0,12	2,8
WR 137	5,85 - 8,20	0,22	3
WR 112	7,05 - 10,0	0,30	3
WR 102	7,00 - 11,0	0,18	3
WR 90	8,20 - 12,4	0,38	3
WR 75	10,0 - 15,0	0,50	3
WR 62	12,4 - 18,0	0,60	3
WR 51	15,0 - 22,0	0,80	3
WR 42	18,0 - 26,5	1,20	3
WR 28	26,5 - 40,0	1,70	3