


Flexco Microwave, Inc.

PO Box 115, 17 Karrville Road
Port Murray, NJ 07865
Telephone 908-835-1720
Fax 908-835-0002
E-mail sales@flexcoMW.com
http://www.FlexcoMW.com



UltraFlex FM402 Flexible Coaxial Cable
Your Flexible Alternative to M17/130-RG402 Semi-Rigid Cable
18 GHz Cable

Frequency vs. Attenuation



Electrical Characteristics:

Nominal Impedance: 50Ω
Velocity of Propagation: 69%
Shielding Effectiveness: -90 dBc min.
Dielectric Withstanding Voltage: 0.5 kV
Nominal Capacitance: 29 pF/ft
Maximum Frequency: 18 GHz
Effective Dielectric Constant: 2.10
Time Delay: 1.5 ns/ft

Physical Characteristics:

Center Cond.: Ag plated, Cu clad steel, 0.037" dia.
Dielectric: Extruded PTFE, 0.117" dia.
Shield One: Flat SPC Strip, 0.130" dia.
Shield Two: #40 AWG SPC, 0.141" dia.
Jacket (Blue): Extruded FEP, 0.163" dia.
Minimum Internal Bend Radius: 1.5 inches
Operating Temperature: -60°C to +200°C
Weight per Foot: 0.032 lbs.
Available Connectors: SMA Straight Plug, SMA Straight Jack, SMA 90° Cube Plug

Frequency (GHz)	Maximum Insertion Loss (dB/ft)	Maximum VSWR	Straight Connector Loss (dB)	Angle Connector Loss (dB)
0.4	0.08	1.15:1	0.02	0.03
1.0	0.15	1.15:1	0.03	0.04
2.0	0.20	1.15:1	0.04	0.05
3.0	0.23	1.20:1	0.04	0.06
5.0	0.29	1.25:1	0.05	0.07
8.0	0.39	1.30:1	0.06	0.11
10.0	0.46	1.30:1	0.07	0.12
12.0	0.50	1.30:1	0.08	0.13
18.0	0.63	1.35:1	0.11	0.15

