

316 SS Pressure Sensor

0-100 mV Output

Gage, Sealed Gage and Absolute
Temperature Compensated

- ▯ Medical Instruments
- ▯ Process Control
- ▯ Waste Water Management
- ▯ Refrigeration/Compressors
- ▯ Pressure Transmitters
- ▯ Level Systems



DESCRIPTION

The Model 154N is a media compatible, compensated, piezoresistive silicon pressure sensor packaged in a 316 stainless steel housing. The sensing package utilizes silicone oil to transfer pressure from the 316 stainless steel diaphragm to the sensing element.

The Model 154N is designed for low pressure applications. A ceramic substrate is attached to the package that contains laser-trimmed resistors for temperature compensation and offset correction. An additional laser-trimmed resistor is included which can be used to adjust sensitivity variations by setting the gain of an external differential amplifier to within $\pm 1\%$ interchangeability.

Alternatives include cap-ring Models 84 or 86, 1/4 NPT Model 96, and Model 85. High pressure sensors are also available.


FEATURES

- ▯ O-Ring Mount
- ▯ 0.1% Pressure Non-linearity
- ▯ -20°C to $+85^{\circ}\text{C}$ Compensated Temperature Range
- ▯ 1.0% Interchangeable Span (provided by gain set resistor)
- ▯ Solid State Reliability
- ▯ Low Power

STANDARD RANGES

Range	psig	psia
0 to 5	Contact Factory	
0 to 15	C	C
0 to 30	C	C
0 to 50	C	C
0 to 100	C	C
0 to 300	C	C
0 to 500	C	C

DIMENSIONS



PERFORMANCE SPECIFICATIONS

All parameters measured at 1.5mA drive and at 25°C after 10 second warm up, unless otherwise specified. Unless specifically indicated, only those parameters indicated as tested are verified on each part. Parameters are specified for the compensated version only.

PARAMETERS	MIN	TYP	MAX	UNITS	NOTES
Full Scale Output Span	75	100	150	mV	1, 2
Zero Offset	-1	0	1	mV	2
Pressure Non-linearity	-0.10		0.10	% Span	3
Pressure Hysteresis	-0.05	0.02	0.05	% Span	
Input Resistance	2,000	3,500	4,500	Ω	
Output Resistance	4000		25000	Ω	
Temperature Error - Span	-0.75		0.75	% Span	4
Temperature Error - Zero	-0.5		0.5	% Span	4, 5
Thermal Hysteresis - Span		0.05		% Span	4
Thermal Hysteresis - Zero		0.05		% Span	4
Long Term Stability - Offset		0.1		±% Span/yr.	
Long Term Stability - Span		0.1		±% Span/yr.	
Supply Current	0.5	1.5	2.0	mA	6
Output Load Resistance	5			MΩ	7
Insulation Resistance (50 VDC)	50			MΩ	8
Pressure Overload			3X	Rated	
Compensated Operating Temperature	-20°C to +85°C				9
Operating Temperature Range	-40°C to +125°C				9
Storage Temperature Range	-50°C to +125°C				9
Media - Pressure Port	Liquids and Gases compatible with 316L Stainless Steel				
Media - Reference Port	Compatible with Silicon, Pyrex, Gold, Fluorosilicone Rubber and 316L Stainless Steel				
Weight	24 g				10

- Notes
1. For amplified output circuits, 3.012V ± 1% interchangeability with gain set resistor. See Application Note TN-003.

2. Measured at vacuum for absolute (A), ambient for gage (G).

3. Best fit straight line.

4. Over Temperature range: -20°C to +85°C Span with respect to +25°C.

5. 15 psi range sensors have a temperature error of ±0.75% (Max) of Zero from -20°C to 85°C.

6. Guarantees output/input ratiometricity.

7. Load resistance to reduce measurement errors due to output loading.

8. Between case and sensing element.

9. Maximum temperature range for product with standard cable and connector is -20°C to +105°C.

10. Weight depends upon configuration (cable, connector).

11. Standard gauge units are not recommended for vacuum applications. For vacuum applications, contact factory.

12. For pressure ranges < 15 psi, consult factory on performance specifications.

ORDERING INFORMATION

154N - 050 G - C T

Vent (T = Tube, Blank is standard = No Tube)

Electrical (C = Ribbon Cable with Connector, P = Solder Pads, R = Ribbon Cable, L = Leads, Uncompensated)

Type (A=Absolute, G=Gage) (Note 11)


Pressure Range (5 to 500 psi, 050 = 50 psi) (Note 12)

Model

CONNECTIONS

PAD NO. / CABLE	FUNCTION
1	+OUT
2	-EX
3	+EX
4	-OUT
5	GAIN
6	GAIN

APPLICATION SCHEMATIC



SUNSTAR 商斯达实业集团是集研发、生产、工程、销售、代理经销、技术咨询、信息服务等为一体的高科技企业，是专业高科技电子产品生产厂家，是具有 10 多年历史的专业电子元器件供应商，是中国最早和最大的仓储式连锁规模经营大型综合电子零部件代理分销商之一，是一家专业代理和分销世界各大品牌 IC 芯片和电子元器件的连锁经营综合性国际公司，专业经营进口、国产名厂名牌电子元件，型号、种类齐全。在香港、北京、深圳、上海、西安、成都等全国主要电子市场设有直属分公司和产品展示展销窗口门市部专卖店及代理分销商，已在全国范围内建成强大统一的供货和代理分销网络。我们专业代理经销、开发生产电子元器件、集成电路、传感器、微波光电元器件、工控机/DOC/DOM 电子盘、专用电路、单片机开发、MCU/DSP/ARM/FPGA 软件硬件、二极管、三极管、模块等，是您可靠的一站式现货配套供应商、方案提供商、部件功能模块开发配套商。商斯达实业公司拥有庞大的资料库，有数位毕业于著名高校——有中国电子工业摇篮之称的西安电子科技大学（西军电）并长期从事国防尖端科技研究的高级工程师为您精挑细选、量身订做各种高科技电子元器件，并解决各种技术问题。

更多产品请看本公司产品专用销售网站：

商斯达中国传感器科技信息网：<http://www.sensor-ic.com/>

商斯达工控安防网：<http://www.pc-ps.net/>

商斯达电子元器件网：<http://www.sunstare.com/>

商斯达微波光电产品网：[HTTP://www.rfoe.net/](http://www.rfoe.net/)

商斯达消费电子产品网：<http://www.icasic.com/>

商斯达实业科技产品网：<http://www.sunstars.cn/>

传感器销售热线：

地址：深圳市福田区福华路福庆街鸿图大厦 1602 室

电话：0755-83370250 83376489 83376549 83607652 83370251 82500323

传真：0755-83376182 (0) 13902971329 MSN: SUNS8888@hotmail.com

邮编：518033 E-mail:szss20@163.com QQ: 195847376

深圳赛格展销部：深圳华强北路赛格电子市场 2583 号 电话：0755-83665529 25059422

技术支持：0755-83394033 13501568376

欢迎索取免费详细资料、设计指南和光盘；产品凡多，未能尽录，欢迎来电查询。

北京分公司：北京海淀区知春路 132 号中发电子大厦 3097 号

TEL: 010-81159046 82615020 13501189838 FAX: 010-62543996

上海分公司：上海市北京东路 668 号上海赛格电子市场 2B35 号

TEL: 021-28311762 56703037 13701955389 FAX: 021-56703037

西安分公司：西安高新开发区 20 所(中国电子科技集团导航技术研究所)

西安劳动南路 88 号电子商城二楼 D23 号

TEL: 029-81022619 13072977981 FAX:029-88789382